



Setting new standards for compact home theatre

Forming the basis of a completely revised Mini Theatre concept, the new M-1 combines a cleaner aesthetic with dramatically improved performance. Combine it with either the ASW608 or the new PV1D subwoofer to create a home theatre experience with superb integration and impressive power for such a discreet system. Plus, its more extended bass response allows M-1 to be used on its own for two-channel applications. Mount the speaker as shown on a table or shelf. Alternatively, a bracket is included for wall mounting and a floor stand is available as an optional extra.



Technical Specifications

Technical features	Nautilus™ tube loaded tweeter with aluminium dome Woven glass fibre cone bass / midrange
Description	2-way vented-box system
Drive units	1x 25mm (1in) aluminium dome high-frequency 1x 100mm (4in) woven glass fibre cone bass / midrange
Frequency range	-6dB at 55Hz and 50kHz
Frequency response	64Hz - 23kHz ±3dB on reference axis
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	85dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 120Hz - 30kHz
Nominal impedance	8Ω (minimum 4.0Ω)
Crossover frequency	4kHz
Recommended amplifier power	20W - 100W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 248mm (9.8in) Width: 114mm (4.5in) Depth: 162mm (6.4in) Mounted on table stand
Net weight	2.3kg (5lb)
Finishes	Cabinet: Matte Black or Matte White Grille: Matte Black or Matte White perforated steel to match



600 SERIES

ASW

SUBWOOFER RANGE

Bowers & Wilkins

The new 600 Series from Bowers & Wilkins transforms your home with pristine sound. Since 1966, we've made technological advances to design the perfect loudspeaker, and our latest innovations bring that heritage to music and movie lovers alike. The 600 Series includes three subwoofers, ranging from the compact ASW608 to the powerful ASW610XP. Each boasts an audiophile-standard, highly efficient Class D amplifier to capture every spine-tingling, water-shaking sound that you hear. Each of our subwoofers are finished to match the rest of the series, with beautiful matte black and white to seamlessly integrate with your home. With the sixth generation of the 600 Series, you can truly transform your space into a beautiful sound session.



ASW610XP

ASW610

ASW608

Technical features	Paper/Aramid Fibre cone drive unit 500W ICEpower® amplifier	Paper/Aramid Fibre cone drive unit 200W ICEpower® amplifier	Paper/Aramid Fibre cone drive unit 200W ICEpower® amplifier
Description	Active closed-box subwoofer system	Active closed-box subwoofer system	Active closed-box subwoofer system
Drive units	ø250mm (10 in) paper/Aramid Fibre cone long-throw	ø250mm (10 in) paper/Aramid Fibre cone long-throw	ø200mm (8 in) paper/Aramid Fibre cone long-throw
Frequency Range	-6dB at 18Hz and 25/140Hz adjustable (EQ at A)	-6dB at 20Hz and 25/140Hz adjustable (EQ at A)	-6dB at 23Hz and 25/140Hz adjustable (EQ at A)
Frequency Response	±3dB 25Hz – 40/140Hz adjustable (EQ at A)	±3dB 27Hz – 40/140Hz adjustable (EQ at A)	±3dB 32Hz – 40/140Hz adjustable (EQ at A)
Bass Extension	-6dB at 18Hz (position A) -6dB at 23Hz (position B) -6dB at 28Hz (position C)	-6dB at 20Hz (position A) -6dB at 25Hz (position B) -6dB at 30Hz (position C)	-6dB at 23Hz (position A) -6dB at 28Hz (position B) -6dB at 36Hz (position C)
Amplifier	Power output: 500W Rated power Consumption: 94W/0.8W standby Input impedance: 33kΩ Signal / noise: >80dB Functions: Input level (line in) Input level (speaker in) Low-pass filter frequency (line in only) Low-pass filter bypass Bass extension Bass roll-off alignment Auto sense on/standby Phase switch Inputs: Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)	Power output: 200W Rated power Consumption: 40W/0.5W standby Input impedance: 33kΩ Signal / noise: >90dB Functions: Input level (line in) Input level (speaker in) Low-pass filter frequency (line in only) Low-pass filter bypass Bass extension Bass roll-off alignment Auto sense on/standby Phase switch Inputs: Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)	Power output: 200W Rated power Consumption: 40W/0.5W standby Input impedance: 33kΩ Signal / noise: >90dB Functions: Volume level (line in) Volume level (speaker in) Low-pass filter frequency (line in only) Low-pass filter bypass Bass extension Bass roll-off alignment Auto sense on/standby Phase switch Inputs: Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)
Low-pass filter	Active 4th -order, variable cut-off frequency	Active 4th -order, variable cut-off frequency	Active 4th -order, variable cut-off frequency
Dimensions	Height: 325mm (12.8 in) not including feet Width: 325mm (12.8 in) Depth: 374mm (14.7 in) including grille and controls	Height: 310mm (12.2 in) not including feet Width: 310mm (12.2 in) Depth: 375mm (14.8 in) including grille and controls	Height: 260mm (10.2 in) not including feet Width: 260mm (10.2 in) Depth: 330mm (13 in) including grille and controls
Net Weight	18.7kg (41.2 lb)	12.5kg (27.6 lb)	8.85kg (19.5 lb)
Finishes	Cabinet: Black White Grille: Black Light Grey	Cabinet: Black White Grille: Black Light Grey	Cabinet: Black White Grille: Black Light Grey