



OPTOTRONIC® OTI DALI DRIVER 15/220-240/1A0 NFC TW I

- Cable clamp housing for independent mounting
- Dimmable on the leading edge and trailing edge
- Housing for independent installation



**NATURE'S
BLUE LIGHT**
the sleep better
bulb



EYE KIND
kind to eyes &
mind



**FULLY
DIMMABLE**
get in the
perfect mood



**CIRCADIAN
FRIENDLY**
natural healthy
light

APPLICATIONS

Residential: All
Architectural: All
Commercial: All



ADVANTAGES

- Control of standard white or Tunable White light acc. DALI device type 8 (DT8)
- TouchDIM Tunable White integrated for use without additional LMS
- Fully programmable via T4T software (NFC, DALI Interface)
- Lifetime: up to 100,000 h (temperature at $T_c = 65^\circ\text{C}$, max. 10 % failure rate)
- High-quality dimming of 1...100 % by amplitude dimming
- High quality of light thanks to <1% output ripple current • Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

AREAS OF APPLICATION

- Classrooms
- Conference rooms
- Daylight simulation for windowless rooms
- For Tunable White as well as for 2-channel use (e.g. direct/indirect lighting)
- Healthcare and hospitality with HCL functionality
- Independent mounting via Cable Clamp Kit possible
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Office with high end HCL functionality
- Suitable for indoor and outdoor SELV installations

Suitable For indoor and outdoor SELV installations