



# Bowers & Wilkins

**HTM71 S3**

Technical Information



## Technical features

Decoupled Carbon Dome tweeter  
Solid Body Tweeter-on-Top  
Continuum™ cone FST midrange  
Aerofoil™ Profile bass cones  
Flowport™

## Description

3-way vented-box system

## Drive units

1x ø25mm (1in) Decoupled Carbon Dome high-frequency  
1x ø100mm (4in) Continuum cone FST midrange  
2x ø165mm (6.5in) Aerofoil Profile bass

## Frequency range

45Hz to 33kHz

## Frequency response

(+/-3dB from reference axis)

50Hz - 28kHz

## Sensitivity

(on axis at 2.83Vrms at 1m)

89dB

## Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)  
<1% 90Hz - 22kHz  
<0.5% 120Hz - 20kHz

## Nominal impedance

8Ω (minimum 3.0Ω)

## Recommended amplifier power

30W - 200W into 8Ω on unclipped programme

## Max. recommended cable impedance

0.1Ω

## Dimensions

Height: 165mm (6.5in) cabinet only  
233mm (9.2in) including tweeter

Width: 628mm (24.7in) cabinet only

Depth: 318mm (12.5in) cabinet only  
356mm (14in) including grille and terminals

## Net weight

17.5kg (38.5lbs)

## Finishes

Cabinet: Gloss black  
Satin white  
Mocha  
Rosenut (APAC only)

Grille: Black  
Grey (Satin White only)