DEFINITIVE TECHNOLOGY®

BP 9000 | SERIES





BP SERIES

EXPLORE A NEW DIMENSION OF SOUND



SOUND THAT TRANSCENDS THE STATUS QUO

The arrival of BP9000 Series ushers true high-performance, full-range sound into a new era—totally redesigned and re-engineered with improvements that cascade across every one of our patented audio technologies. From advances in our Forward Focused Bipolar Array, built-in powered subwoofers, new Intelligent Bass Control, and seamless Dolby Atmos® / DTS:X integration™, the BP9000 Series offers the big, room-filling, yet precise sound you demand with an elegant footprint that makes every single day of ownership a marvel to behold.

BP SERIES



BP9080x

High-Performance Tower Speaker with Integrated 12" Powered Subwoofer and Height Module

- (5) 5.25" (133 mm) bass/mid drivers
- (3) 1" (25 mm) dome tweeters
- (1) 12" (305 mm) subwoofer
- (2) 12" (305 mm) sub radiators
- 51.5" H x 12" W x 16" D (130.8cm H x 30.5 cm W x 40.6 cm D)



BP9060

High-Performance Tower Speaker with Integrated 10" Powered Subwoofer

- (3) 4.5" (114 mm) bass/mid drivers
- (2) 1" (25 mm) dome tweeters
- (1) 10" (254 mm) subwoofer
- (2) 10" (254 mm) sub radiators
- Measures 44.5" H x 11" W x 13" D (113.1cm H x 15.3 cm W x 33 cm D)



BP9040

High-Performance Tower Speaker with Integrated 8" Powered Subwoofer

- (3) 4.5" (114 mm) bass/mid drivers
- (2) 1" (25 mm) dome tweeters
- (1) 8" (203 mm) subwoofer
- (2) 8" (203 mm) sub radiators
- Measures 39" H x 11" W x 13" D (99.0cm H x 27.9 cm W x 33 cm D



BP9020

High-Performance Tower Speaker with Integrated 8" Powered Subwoofer

- (3) 3.5" (89 mm) bass/mid drivers
- (1) 1" (25 mm) dome tweeter
- (1) 8" (203 mm) subwoofer
- Measures 35.5" H x 11" W x 13" D (88.3cm H x 27.9 cm W x 33 cm D)



A90

High-Performance Height Speaker Module for Dolby Atmos/DTS:X (Compatible with BP9020, BP9040, BP9060)

- (1) 4.5" (114 mm) bass/mid drivers
- (1) 1" (25 mm) dome tweeters
- Measures 3.75" H x 6" W x 13" D (95 mm x 152 mm x 33 mm)



CS9080

High-Performance Center Channel Speaker with Integrated 8" Powered Subwoofer and Bass Radiator

- (2) 5.25" (133 mm) bass/mid drivers
- (1) 1" (25 mm) dome tweeter
- (1) 8" (203 mm) subwoofer
- (2) 10" (254 mm) bass radiator
- Measures 7" H x 23" W x 14.25" D (178 mm H x 58.4 mm W x 36.2 mm D)



CS9060

High-Performance Center Channel Speaker with Integrated 8" Powered Subwoofer

- (2) 4.5" (114 mm) bass/mid drivers
- (1) 1" (25 mm) dome tweeter
- (1) 8" (203 mm) subwoofer
- Measures 5.95" H x 20.75" W x 12" D (151 mm H x 527 mm W x 304 mm D)



CS9040

High-Performance Center Channel Speaker with Integrated 8" Bass Radiator

- (2) 4.5" (114 mm) bass/mid drivers
- (1) 1" (25 mm) dome tweeter
- (1) 8" (203 mm) subwoofer
- Measures 5.95" H x 20.75" W x 12" D
 (151 mm H x 527 mm W x 304 mm D)

BP SERIES (CONT.)



SR9080

High-Performance Bipolar Surround Speaker

- (2) 4.5" (114 mm) bass/mid drivers
- (2) 1" (25 mm) dome tweeters
- Measures 15.63" H x 9" W x 6.06" D (397 mm x 229 mm x 154 mm)



BP10B

Bipolar Tower Speaker

- (2) 6.5" (165 mm) bass/mid drivers
- (2) 1" (25 mm) dome tweeters
- Measures 42" H x 8" W x 12.25" D (1067 mm x 203 mm x 311 mm)



SR9040

High-Performance Bipolar Surround Speaker

- (2) 3.5" (89 mm) bass/mid drivers
- (2) 1" (25 mm) dome tweeters
- Measures 9.5" H x 7.81" W x 5.38"
 D (241 mm x 198 mm x 137 mm)



BP6B

Bipolar Tower Speaker

- (2) 5.25" (133 mm) bass/mid drivers
- (2) 1" (25 mm) dome tweeters
- Measures 35" H x 7" W x 11" D (889 mm x 179 mm x 279 mm)



www.definitivetech.com

DISTRIBUTOR LANGUAGE HERE

In consed magnist, experes simusame sollo enia doluptati vollique dolorem invenihit, sunt fuga. Itatur atur aliquaeped moless