Bowers & Wilkins



See nothing, hear everything

Need big sound, slamming bass and audiophile bass extension, but don't want to see where it comes from? Then the new ISW-4 in-wall subwoofer is the product for you. Its two long-throw 200mm drivers allows the ISW-4 to move large volumes of air needed for high-quality low-frequency output, but is nicely hidden away inside a wall. Powered by a separate audiophile-standard 250W Class D amplifier the SA250 Mk2, the system keeps its cool even when the music movie action is whipping up a storm.

ISW-4 Technical Specifications

Description	In wall subwoofer system with external rack- mount amplifier
Drive units	2 x 200mm (8 in) Paper/Aramid Fibre cone
Frequency range	-6dB at 17Hz and 290Hz adjustable (EQ at A)
Frequency response	±3dB 21Hz - 200Hz adjustable (EQ at A)
Bass extension	-6dB at 17Hz (position A) -6dB at 21Hz (position B) -6dB at 24Hz (position C)
Power Handling	200W 8 Ω (minimum 6.3 Ω)
Dimensions	Height: 494mm (19.5 in) Width: 264mm (10.4 in)
Cut-out size	Height: 485mm (19 in) Width: 255 (10 in)
Net weight	6.4kg (14.1lb)
Finish Frame/Grille	Semi-matt white suitable for customising or pre-painting
Accessories	Pre-mount kit for new construction
Back Box	
Box	Height: 1406mm (55.4 in) Width: 345mm (13.6 in) Depth: 85mm (3.4 in)
Net Weight	9.6kg (21.2lb)
Material	MDF

Custom Installation SA250 Mk2



SA250 Mk2 Technical Specifications

Description	250W rack-mount amplifier with built-in sub- woofer equalisation
Amplifier inputs	 2x RCA Phono socket, line in 2x RCA Phono socket, link out 1x XLR socket, line in 1x XLR socket, link out 3.5mm jack - 12V trigger on/standby (overrides manual standby setting) 3.5mm jack - 12V trigger equalisation movie/music
Amplifier outputs	 1x Neutrik[®] Speakon[®] 4-pole speaker socket 2x pairs of Binding Posts
Amplifier power output	250W
Input impedance	33kΩ
Signal / noise	>80dB
Rated power consumption	95W – 1/8 full power 30W – Idling
Dimensions	Height: 100mm (3.9 in) [88.5mm (3.5 in) plus feet]
	Width: 430mm (16.9 in) Depth: 322mm (12.7 in) Front panel Height: 2U 88.1mm/3.5 in
Net weight	5.4kg (11.9 lb)
Finish	Black

Bowers & Wilkins

www.bowers-wilkins.com

Speakon is a registered trademark of Neutrik AG Copyright © B&W Group Ltd. E&OE B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments